



| REV | DESCRIPTION | DATE |
|-----|-------------|----------------|
| △ | RDK-97127 | 張馨尹 2009/12/15 |
| △ | RDK-98020 | 張馨尹 2009/12/15 |

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

| | | | | |
|--------|----|----|----|----|
| A.W.G. | 22 | 20 | 18 | 16 |
| AMP. | 9 | 12 | 17 | 18 |
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : RED
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 22-16 A.W.G. (0.5-1.5 mm²)
 7. TERMINAL SURFACE TREATMENT : TIN PLATED
 8. TERMINAL THICKNESS : 0.75 mm

| | |
|---------------------|-----------------|
| △ Tolerance Unless | |
| Otherwise Specified | |
| 0 > | mm ± ANGLE |
| > | mm ± 0° ° REF ± |
| > | mm ± ° ° ± |
| > | mm ± ° ° ± |

| | | | | | |
|----------|--|----------|-------|---------|-----------|
| NAME | VINYL-INSULATED (EASY ENTRY) BLADE TERMINALS | | | UNIT | mm |
| PART NO. | DVBL1-10-2.3 | MATERIAL | ----- | APPROVE | |
| NUMBER | KA-980278-C | SCALE | SHEET | PAGE | CHECKED |
| DATE | 2009/07/31 | 4/1 | 1-2 | 10F2 | DRAWN 謝婉如 |