



REV	DESCRIPTION	DATE
△	RDK-97048	張馨尹 2008/09/12
△	RDK-97127	張馨尹 2008/09/12
△	RDK-98020	張馨尹 2009/07/24
△	RDCM-105170	郭碧紋 2016/11/17

NOTE :

1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	9	12	17	18
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : RED
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 22-16 A.W.G. ( 0.5-1.5 mm<sup>2</sup> )
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.75 mm

Tolerance Unless	
Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED (EASY ENTRY) SPADE TERMINALS				UNIT	mm	
PART NO.	DVF1-3	MATERIAL	-----	APPROVE			
NUMBER	KA-95652-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2006/06/22	4/1	1-4	10F1	DRAWN	張馨尹	