



| REV | DESCRIPTION | DATE           |
|-----|-------------|----------------|
| △   | RDK-97048   | 謝婉如 2008/06/13 |
| △   | RDK-97127   | 謝婉如 2009/04/09 |
| △   | RDK-98020   | 謝婉如 2009/04/09 |

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : 

|        |    |    |    |    |
|--------|----|----|----|----|
| A.W.G. | 22 | 20 | 18 | 16 |
| AMP.   | 9  | 12 | 17 | 18 |
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : RED
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 22-16 A.W.G. ( 0.5-1.5 mm<sup>2</sup> )
  7. TERMINAL SURFACE TREATMENT : TIN PLATED
  8. TERMINAL THICKNESS : 0.75 mm

|                       |               |
|-----------------------|---------------|
| △ Tolerance Unless    |               |
| □ otherwise Specified |               |
| 0 >                   | mm ± ANGLE    |
| >                     | mm ± 0° REF ± |
| >                     | mm ± ° ±      |
| >                     | mm ± ° ±      |

|          |   |          |            |         |     |
|----------|---|----------|------------|---------|-----|
| NAME     | VINYL-INSULATED LOCKING SPADE TERMINALS |          |            | UNIT    | m   |
| PART NO. | DVF1-4LF                                | MATERIAL | -----      | APPROVE |     |
| NUMBER   | KA-95361-C                              | SCALE    | SHEET PAGE | CHECKED |     |
| DATE     | 2006/05/15                              | 4/1      | 1-3 10F2   | DRAWN   | 張馨尹 |