



REV	DESCRIPTION	DATE
△	RDK-97048	張馨尹 2009/07/24
△	RDK-97127	張馨尹 2009/07/24
△	RDK-98020	張馨尹 2009/07/24

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	16	14	
AMP.	18	30	
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : BLUE
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 16-14 A.W.G. ( 1.5-2.5 mm<sup>2</sup> )
  7. TERMINAL SURFACE TREATMENT : TIN PLATED
  8. TERMINAL THICKNESS : 0.80 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED (EASY ENTRY) SPADE TERMINALS			UNIT	mm	
PART NO.	DVF2-4	MATERIAL	-----	APPROVE		
NUMBER	KA-95667-C	SCALE	SHEET PAGE	CHECKED		
DATE	2006/06/22	4/1	1-3 10F2	DRAWN	張馨尹	