



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2008/03/13
△	RDK-97127	張馨尹 2008/11/12
△	RDK-98020	張馨尹 2009/04/24
△	RDC-98308	謝婉如 2009/06/10

NOTE :

1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	9	12	17	18
- △ 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : RED
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 22-16 A.W.G. ( 0.5-1.5 mm<sup>2</sup> )
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.75 mm

Tolerance Unless	
△ Otherwise Specified	
0 >	mm ±
>	mm ±
>	mm ±
>	mm ±
>	mm ±
ANGLE	
0°	REF ±
°	±
°	±

NAME	VINYL-INSULATED (EASY ENTRY) PIN TERMINALS			UNIT	mm
PART NO.	DVP1-12	MATERIAL	-----	APPROVE	
NUMBER	KA-95697-C	SCALE	SHEET PAGE	CHECKED	
DATE	2006/06/22	4/1	1-4 10F1	DRAWN	張馨尹