



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2008/03/13
△	RDK-97127	張馨尹 2008/11/12
△	RDK-98020	張馨尹 2009/04/24
△	RDC-98308	謝婉如 2009/06/10

NOTE :
 1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14
AMP.	18	30

- △ 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
- 3. INSULATION MATERIAL : VINYL
- 4. INSULATION COLOR : BLUE
- 5. TERMINAL MATERIAL : COPPER
- 6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
- 7. TERMINAL SURFACE TREATMENT : TIN PLATED
- 8. TERMINAL THICKNESS : 0.80 mm

Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED (EASY ENTRY) PIN TERMINALS			UNIT	mm
PART NO.	DVP2-9R	MATERIAL	-----	APPROVE	
NUMBER	KA-95701-C	SCALE	SHEET PAGE	CHECKED	
DATE	2006/06/22	4/1	1-4 10F1	DRAWN	張馨尹