



REV	DESCRIPTION	DATE
△	RDK-97048	張善尹 2009/08/21
△	RDK-97127	張善尹 2009/08/21
△	RDK-98020	張善尹 2009/08/21
△	RDCM-104114	郭碧紋 2015/09/18

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14
AMP.	18	30
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.80 mm

△ Tolerance Unless	
Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED (EASY ENTRY) RING TERMINALS			UNIT	mm	
PART NO.	DVR2-37	MATERIAL	-----	APPROVE		
NUMBER	KA-951268-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2006/11/29	4/1	1-4	10F1	DRAWN	謝婉如