



REV	DESCRIPTION	DATE
△	RDK-97048	張馨尹 2009/08/21
△	RDK-97127	張馨尹 2009/08/21
△	RDK-98020	張馨尹 2009/08/21

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14	
AMP.	18	30	
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : BLUE
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
 7. TERMINAL SURFACE TREATMENT : TIN PLATED
 8. TERMINAL THICKNESS : 0.80 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED (EASY ENTRY) RING TERMINALS			UNIT	mm	
PART NO.	DVR2-6	MATERIAL	-----	APPROVE		
NUMBER	KA-951275-C	SCALE	SHEET PAGE	CHECKED		
DATE	2007/04/27	4/1	1-3 10F2	DRAWN	張馨尹	

INC.