



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2008/03/12
△	RDK-97127	張馨尹 2008/08/15
△	RDK-98020	張馨尹 2009/08/21

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	12	10	
AMP.	35	50	
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : YELLOW
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 12-10 A.W.G. ( 4 - 6 mm<sup>2</sup> )
  7. TERMINAL SURFACE TREATMENT : TIN PLATED
  8. TERMINAL THICKNESS : 1.00 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED (EASY ENTRY) RING TERMINALS				UNIT	mm	
PART NO.	DVR5-10	MATERIAL	-----	APPROVE			
NUMBER	KA-951787-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2008/03/11	3/1	1-3	10F2	DRAWN	謝婉如	