



REV	DESCRIPTION	DATE
△	RDK-97048	張譽尹 2008/08/15
△	RDK-97127	張譽尹 2008/08/15
△	RDK-98020	張譽尹 2009/08/21
△	RDCM-105167	林淑祺 2017/06/27

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :  $\frac{\text{A.W.G.} \begin{matrix} 12 & 10 \\ \text{AMP.} & 35 & 50 \end{matrix}}$
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : YELLOW
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 12-10 A.W.G. ( 4 - 6 mm<sup>2</sup> )
  7. TERMINAL SURFACE TREATMENT : TIN PLATED
  8. TERMINAL THICKNESS : 1.00 mm

Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° > ° REF ±
>	mm ± ° > ° ±
>	mm ± ° > ° ±

NAME	VINYL-INSULATED (EASY ENTRY) RING TERMINALS			UNIT	mm	
PART NO.	DVR5-8	MATERIAL	-----	APPROVE		
NUMBER	KA-951786-C	SCALE	SHEET PAGE	CHECKED		
DATE	2007/04/16	2/1	1-4 1DF1	DRAWN	吳金賢	