



REV	DESCRIPTION	DATE
△	RDK-97048	張馨尹 2008/06/02
△	RDK-97127	張馨尹 2008/11/14
△	RDK-98020	張馨尹 2009/12/15

- NOTE:
1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	9	12	17	18
  2. MAXIMUM ELECTRICAL RATING : △ 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : RED
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 22-16 A.W.G.( 0.5-1.5 mm<sup>2</sup>)
  7. TERMINAL SURFACE TREATMENT : TIN PLATED
  8. TERMINAL THICKNESS : 0.75 mm

△	Tolerance Unless otherwise Specified
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED BLADE TERMINALS				UNIT	mm	
PART NO.	VBL1-9-28	MATERIAL	-----	APPROVE			
NUMBER	KA-951153-C	SCALE	SHEET PAGE	CHECKED			
DATE	2006/08/21	4/1	1-3 10F2	DRAWN	張馨尹		