



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2008/06/27
△	RDK-97127	張馨尹 2009/12/25
△	RDK-98020	張馨尹 2009/12/25
△	RDC-98791	張馨尹 2009/12/25

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : $\frac{\text{A.W.G.} \mid 16 \mid 14}{\text{AMP.} \mid 18 \mid 30}$
 2. MAXIMUM ELECTRICAL RATING : $\triangle 105^{\circ}\text{C}$ 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : BLUE
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
 7. TERMINAL SURFACE TREATMENT : TIN PLATED
 8. TERMINAL THICKNESS : 0.80 mm

Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED TIPPED BLADE TERMINALS			UNIT	mm
PART NO.	VLH2-17-46	MATERIAL	-----	APPROVE	
NUMBER	KA-95134-C	SCALE	SHEET PAGE	CHECKED	
DATE	2006/03/24	4/1	1-4 10F2	DRAWN	張馨尹