



REV	DESCRIPTION	DATE
△ RDK-97127		張馨尹 2008/11/12
△ RDK-98020		張馨尹 2009/12/14
△ RDC-99217		張馨尹 2010/07/02

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	12	10	
AMP.	35	50	
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : YELLOW
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 12-10 A.W.G. (4 - 6 mm²)
 7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
 8. TERMINAL SURFACE TREATMENT : TIN PLATED
 9. TERMINAL THICKNESS : 1.00 mm

Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP BLADE TERMINALS			UNIT	mm
PART NO.	VDBL5-10-28	MATERIAL	-----	APPROVE	
NUMBER	KA-96640-C	SCALE	SHEET PAGE	CHECKED	
DATE	2007/09/17	4/1	1-3 10F2	DRAWN	張馨尹