



REV	DESCRIPTION	DATE
△	RDK-97127	張馨尹 2008/11/12
△	RDK-98020	張馨尹 2009/12/14
△	RDC-99217	張馨尹 2010/07/02

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	12	10	
AMP.	35	50	
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : YELLOW
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 12-10 A.W.G. (4 - 6 mm²)
7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
8. TERMINAL SURFACE TREATMENT : TIN PLATED
9. TERMINAL THICKNESS : 1.00 mm

Tolerance Unless	
△ Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP BLADE TERMINALS			UNIT	mm
PART NO.	VDBL5-14-45	MATERIAL	-----	APPROVE	
NUMBER	KA-96642-C	SCALE	SHEET	PAGE	CHECKED
DATE	2007/09/17	4/1	1-3	10F2	DRAWN 張馨尹