



REV	DESCRIPTION	DATE
	RDK-109046	楊駿為 2020/09/08

NOTE:

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16
AMP.	9	12	17	18
2. MAXIMUM ELECTRICAL RATING : 75°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : RED
5. TERMINAL MATERIAL : COPPER PLATE
6. WIRE RANGE : 22-16 A.W.G.(0.5-1.5mm²)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL

Tolerance Unless Otherwise Specified	
0 > 6 mm ± 0.20	ANGLE
6 > 18 mm ± 0.30	0° REF ±
18 > 30 mm ± 0.40	° ±
30 > 75 mm ± 0.50	° ±

NAME	VINYL-INSULATED DOUBLE CRIMP BUTT SPLICE CONNECTORS			UNIT	mm	
PART NO.	VDBT1	MATERIAL	-----	APPROVE	張馨尹	
NUMBER	KA-95967-C	SCALE	REV.	SHEET	CHECKED	張馨尹
DATE	2006/07/21	4/1	1-1	10F1	DRAWN	張馨尹