



REV	DESCRIPTION	DATE
△	RDK-97127	2008/11/12
△	RDK-98020	2009/06/15
△	RDC-98308	2009/06/15
△	RDC-99217	2010/06/29

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16
AMP.	9	12	17	30
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : RED
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 22-16 A.W.G. (0.5-1.5 mm²)
 7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
 8. TERMINAL SURFACE TREATMENT : TIN PLATED
 9. TERMINAL THICKNESS : 0.75 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ±
>	mm ±
>	mm ±
>	mm ±
ANGLE	
0°	REF ±
°	±
°	±

NAME	VINYL-INSULATED DOUBLE CRIMP PIN TERMINALS				UNIT	mm	
PART NO.	VDPN1-9	MATERIAL	-----	APPROVE			
NUMBER	KA-961214-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2007/11/20	4/1	1-4	10F1	DRAWN		