



REV	DESCRIPTION	DATE
△	RDK-97127	謝婉如 2009/08/25
△	RDK-98020	謝婉如 2009/08/25
△	RDC-99217	謝婉如 2010/06/18

NOTE :

1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	9	12	17	18
- △ 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : RED
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 22-16 A.W.G. ( 0.5-1.5 mm<sup>2</sup> )
7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
8. TERMINAL SURFACE TREATMENT : TIN PLATED
9. TERMINAL THICKNESS : 0.75 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP RING TERMINALS				UNIT	mm	
PART NO.	VDR1-6	MATERIAL	-----	APPROVE			
NUMBER	KA-94243-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2007/06/14	4/1	1-3	10F2	DRAWN	張馨尹	