



| REV | DESCRIPTION | DATE |
|-----|-------------|----------------|
| △ | RDK-97127 | 謝婉如 2009/08/25 |
| △ | RDK-98020 | 謝婉如 2009/08/25 |
| △ | RDC-99217 | 謝婉如 2010/06/21 |

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

| | | | |
|--------|----|----|--|
| A.W.G. | 16 | 14 | |
| AMP. | 18 | 30 | |
- △ 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
8. TERMINAL SURFACE TREATMENT : TIN PLATED
9. TERMINAL THICKNESS : 0.80 mm

| Tolerance Unless Otherwise Specified | |
|--------------------------------------|-----------------|
| 0 > | mm ± ANGLE |
| > | mm ± 0° ° REF ± |
| > | mm ± ° ° ± |
| > | mm ± ° ° ± |

| | | | | | | | |
|----------|--|----------|-------|---------|---------|-----|--|
| NAME | VINYL-INSULATED DOUBLE CRIMP RING TERMINAL | | | | UNIT | mm | |
| PART NO. | VDR2-6 | MATERIAL | ----- | APPROVE | | | |
| NUMBER | KA-94258-C | SCALE | SHEET | PAGE | CHECKED | | |
| DATE | 2007/09/14 | 4/1 | 1-3 | 10F2 | DRAWN | 張馨尹 | |