



REV	DESCRIPTION	DATE
△	RDK-97127	謝婉如 2009/08/25
△	RDK-98020	謝婉如 2009/08/25
△	RDC-99217	謝婉如 2010/06/21
△	RDJ-105194	郭碧紋 2016/08/02

NOTE:

- MAXIMUM ELECTRIC CURRENT : 

A.W.G.	12	10
AMP.	35	50
- MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
- INSULATION MATERIAL : VINYL
- INSULATION COLOR : YELLOW
- TERMINAL MATERIAL : COPPER
- WIRE RANGE : 12-10 A.W.G.( 4-6 mm<sup>2</sup>)
- TERMINAL SURFACE TREATMENT : TIN PLATED
- TERMINAL THICKNESS : 1.0 mm

△	tolerance Unless
□	otherwise Specified
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP RING TERMINALS				UNIT	mm	
PART NO.	VDR5-6	MATERIAL	-----	APPROVE			
NUMBER	KA-94288-C	SCALE	SHEET PAGE	CHECKED			
DATE	2006/07/06	2/1	1-4 10F1	DRAWN	張馨尹		