



REV	DESCRIPTION	DATE
△	RDK-97127	謝婉如 2009/08/25
△	RDK-98020	謝婉如 2009/08/25
△	RDC-99217	謝婉如 2010/06/21
△	RDCM-106052	林淑慎 2017/04/14

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14
AMP.	18	30
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
8. TERMINAL SURFACE TREATMENT : TIN PLATED
9. TERMINAL THICKNESS : 0.80 mm

△	Tolerance Unless	
□	Otherwise Specified	
0 >	mm ±	ANGLE
>	mm ±	0° ° REF ±
>	mm ±	° ° ±
>	mm ±	° ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP RING TERMINAL				UNIT	mm
PART NO.	VDRL2-4	MATERIAL	-----	APPROVE		
NUMBER	KA-94255-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2007/09/14	4/1	1-4	10F1	DRAWN	張馨尹