



REV	DESCRIPTION	DATE
△	RDK-97127	謝婉如 2009/08/25
△	RDK-98020	謝婉如 2009/08/25
△	RDC-99217	謝婉如 2010/06/21
△	RDCM-102040	張馨尹 2013/10/21
△	RDCM-107083	林淑禎 2018/07/11

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14
AMP.	18	30
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
8. TERMINAL SURFACE TREATMENT : TIN PLATED
9. TERMINAL THICKNESS : 0.80 mm

△	Tolerance Unless otherwise Specified	
0 >	mm ±	ANGLE
>	mm ±	0° ° REF ±
>	mm ±	° ° ±
>	mm ±	° ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP RING TERMINAL				UNIT	mm	
PART NO.	VDRL2-5	MATERIAL	-----	APPROVE	黃智奇		
NUMBER	KA-94257-C	SCALE	REV. SHEET	CHECKED	柯輝強		
DATE	2007/01/04	4/1	1-5 10F1	DRAWN	張馨尹		