



REV	DESCRIPTION	DATE
△	RDK-97127	謝婉如 2009/08/25
△	RDK-98020	謝婉如 2009/08/25
△	RDC-99217	謝婉如 2010/06/18

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16
AMP.	9	12	17	18
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : RED
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 22-16 A.W.G. (0.5-1.5 mm²)
7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
8. TERMINAL SURFACE TREATMENT : TIN PLATED
9. TERMINAL THICKNESS : 0.75 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ±
>	mm ±
>	mm ±
>	mm ±
	ANGLE
	0° REF ±
	° ±
	° ±

NAME	VINYL-INSULATED DOUBLE CRIMP RING TERMINALS				UNIT	mm	
PART NO.	VDRM1-3.7	MATERIAL	-----	APPROVE			
NUMBER	KA-94237-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2005/03/29	4/1	1-3	10F2	DRAWN	張馨尹	