



REV	DESCRIPTION	DATE
△	RDK-97127	2009/08/25
△	RDK-98020	2009/08/25
△	RDC-99217	2010/06/18
△	RDCM-105125	2017/10/17

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16
AMP.	9	12	17	18
- △ 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : RED
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 22-16 A.W.G. (0.5-1.5 mm²)
7. DOUBLE CRIMP : WITH SHORT COPPER SLEEVE ON BARREL
8. TERMINAL SURFACE TREATMENT : TIN PLATED
9. TERMINAL THICKNESS : 0.75 mm

Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP RING TERMINALS				UNIT	mm
PART NO.	VDRS1-4	MATERIAL	----	APPROVE	<i>[Signature]</i>	
NUMBER	KA-94239-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2007/08/06	4/1	1-4	10F1	DRAWN	