



REV	DESCRIPTION	DATE
△	RDK-97127	謝婉如 2009/08/25
△	RDK-98020	謝婉如 2009/08/25
△	RDC-99217	謝婉如 2010/06/21
△	RDJ-104045	吳加鋒 2015/07/06
△	RDCM-106011	林佳麗 2017/03/06

NOTE :

- MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14
AMP.	18	30
- MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
- INSULATION MATERIAL : VINYL
- INSULATION COLOR : BLUE
- TERMINAL MATERIAL : COPPER
- WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
- DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
- TERMINAL SURFACE TREATMENT : TIN PLATED
- TERMINAL THICKNESS : 0.80 mm

△	Tolerance Unless otherwise Specified	
0 >	mm ±	ANGLE
>	mm ±	0° REF ±
>	mm ±	° ±
>	mm ±	° ±

NAME	VINYL-INSULATED DOUBLE CRIMP RING TERMINAL				UNIT	mm	
PART NO.	VDRS2-4	MATERIAL	-----	APPROVE			
NUMBER	KA-94254-C	SCALE	SHEET PAGE	CHECKED			
DATE	2007/09/14	4/1	1-5 10F1	DRAWN	張馨尹		