



REV	DESCRIPTION	DATE
△	RDK-97127	謝婉如 2009/08/24
△	RDK-98020	謝婉如 2009/08/24
△	RDC-99217	張馨尹 2010/06/29

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	9	12	17	18
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : RED
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 22-16 A.W.G. ( 0.5-1.5 mm<sup>2</sup> )
  7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
  8. TERMINAL SURFACE TREATMENT : TIN PLATED
  9. TERMINAL THICKNESS : 0.75 mm

△	Tolerance Unless otherwise Specified	
0 >	mm ±	ANGLE
>	mm ±	0° > ° REF ±
>	mm ±	° > ° ±
>	mm ±	° > ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP SPADE TERMINALS				UNIT	mm	
PART NO.	VDS1-32	MATERIAL	-----	APPROVE			
NUMBER	KA-94600-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2007/06/05	4/1	1-3	10F2	DRAWN	張馨尹	