



REV	DESCRIPTION	DATE
△	RDK-97127	謝婉如 2009/08/24
△	RDK-98020	謝婉如 2009/08/24
△	RDC-99217	張馨尹 2010/06/29

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16
AMP.	9	12	17	18
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : RED
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 22-16 A.W.G. (0.5-1.5 mm²)
 7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
 8. TERMINAL SURFACE TREATMENT : TIN PLATED
 9. TERMINAL THICKNESS : 0.75 mm

△ Tolerance Unless	
□ Otherwise Specified	
0 >	mm ±
>	mm ±
>	mm ±
>	mm ±
ANGLE	
0°	° REF ±
°	° ±
°	° ±

NAME	VINYL-INSULATED DOUBLE CRIMP SPADE TERMINALS				UNIT	mm
PART NO.	VDSS1-3.7	MATERIAL	-----	APPROVE		
NUMBER	KA-94601-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2005/03/29	4/1	1-3	10F2	DRAWN	張馨尹