



REV	DESCRIPTION	DATE
△ RDK-96131		張馨尹 2008/01/03
△ RDK-98053		洗勝賢 2009/03/17

NOTE :

- MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16
AMP.	3	4	7	10
- MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
- INSULATION MATERIAL : VINYL
- INSULATION COLOR : RED
- TERMINAL MATERIAL : BRASS
- WIRE RANGE : 22-16 A.W.G. ($0.5-1.5 \text{ mm}^2$)
- NEMA TAB : 0.032 inch * 0.110 inch ($0.8 \text{ mm} * 2.80 \text{ mm}$)
- DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
- TERMINAL SURFACE TREATMENT : TIN PLATED
- TERMINAL THICKNESS : 0.30 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ±0.20	ANGLE
6 > 18 mm ±0.30	0° REF ±
18 > 30 mm ±0.40	° ±
30 > 75 mm ±0.50	° ±

NAME	VINYL-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS				UNIT	APPROVE
PART NO.	VF1-110-8	MATERIAL	-----	APPROVE	[Signature]	
NUMBER	KA-951302-C	SCALE	SHEET	PAGE	CHECKED	[Signature]
DATE	2006/09/08	4/1	1-2	10F2	DRAWN	謝婉如