



REV	DESCRIPTION	DATE
△	RDK-96131	張馨尹 2008/01/03

NOTE :

1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	16	14	
AMP.	10	15	
2. MAXIMUM ELECTRICAL RATING : △ 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : BRASS
6. WIRE RANGE : 16-14 A.W.G. ( 1.5-2.5 mm<sup>2</sup> )
7. NEMA TAB : 0.020 inch \* 0.110 inch ( 0.5 mm \* 2.80 mm )
8. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
9. TERMINAL SURFACE TREATMENT : TIN PLATED
10. TERMINAL THICKNESS : 0.30 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ± 0.20	ANGLE
6 > 18 mm ± 0.30	0° REF ±
18 > 30 mm ± 0.40	° ±
30 > 75 mm ± 0.50	° ±

NAME	VINYL-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS				UNIT	
PART NO.	VF2-110-5	MATERIAL	-----	APPROVE		
NUMBER	KA-951309-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2007/04/18	4/1	1-1	10F2	DRAWN	張馨尹