



REV	DESCRIPTION	DATE
△	RDK-96131	張馨尹 2008/01/04
△	RDC-100346	張馨尹 2011/11/08
△	RDK-93023	張馨尹 2011/11/15
△	RDK-100102	張馨尹 2011/12/08

NOTE :

- MAXIMUM ELECTRIC CURRENT : 

A.W.G.	12	10
AMP.	20	24
- MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
- INSULATION MATERIAL : VINYL
- INSULATION COLOR : YELLOW
- TERMINAL MATERIAL : BRASS
- WIRE RANGE : 12-10 A.W.G. ( 4 - 6 mm<sup>2</sup> )
- NEMA TAB : 0.020 inch \* 0.110 inch ( 0.5 mm \* 2.80 mm )
- DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
- TERMINAL SURFACE TREATMENT : TIN PLATED
- TERMINAL THICKNESS : 0.35 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ± 0.20	ANGLE
6 > 18 mm ± 0.30	0° REF ±
18 > 30 mm ± 0.40	° ±
30 > 75 mm ± 0.50	° ±

NAME	VINYL-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS				UNIT	mm
PART NO.	VF5-110-5	MATERIAL	-----	APPROVE		
NUMBER	KA-951318-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2008/01/04	4/1	1-4	10F2	DRAWN	張馨尹