



REV	DESCRIPTION	DATE
△	RDK-96131	張馨尹 2008/01/04
△	RDCM-108002	林淑楨 2019/05/20

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	12	10
AMP.	20	24
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : YELLOW
  5. TERMINAL MATERIAL : BRASS
  6. WIRE RANGE : 12-10 A.W.G. ( 4 - 6 mm<sup>2</sup> )
  7. NEMA TAB : 0.032 inch \* 0.250 inch ( 0.8 mm \* 6.35 mm )
  8. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
  9. TERMINAL SURFACE TREATMENT : TIN PLATED
  10. TERMINAL THICKNESS : 0.40 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ± 0.20	ANGLE
6 > 18 mm ± 0.30	0° ° REF ±
18 > 30 mm ± 0.40	° ° ±
30 > 75 mm ± 0.50	° ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS			UNIT	mm	
PART NO.	VF5-250	MATERIAL	-----	APPROVE		
NUMBER	KA-951322-C	SCALE	REV.	SHEET	CHECKED	
DATE	2006/09/07	4/1	1-2	10F1	DRAWN	謝婉如