



REV	DESCRIPTION	DATE
△	RDK-94275	2008/01/10
△	RDK-96131	2008/01/10
△	RDC-102187	2013/11/07

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14
AMP.	10	15
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : BLUE
 5. TERMINAL MATERIAL : BRASS
 6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
 7. NEMA TAB : 0.032 inch * 0.250 inch (0.8 mm * 6.35 mm)
 8. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
 9. TERMINAL SURFACE TREATMENT : TIN PLATED
 10. TERMINAL THICKNESS : 0.40 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ± 0.20	ANGLE
6 > 18 mm ± 0.30	0° REF ±
18 > 30 mm ± 0.40	° ±
30 > 75 mm ± 0.50	±

NAME	VINYL-FULLY INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS				UNIT	
MATERIAL	-----				APPROVE	
NUMBER	KA-94342-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2006/03/27	3/1	1-3	10F2	DRAWN	