



REV	DESCRIPTION	DATE
△	RDK-96131	張馨尹 2008/01/10
△	RDCM-102188	謝婉如 2013/11/11

NOTE :

- MAXIMUM ELECTRIC CURRENT : 

A.W.G.	12	10
AMP.	20	24
- MAXIMUM ELECTRICAL RATING :  $105^{\circ}\text{C}$  600 VOLTS MAX.
- INSULATION MATERIAL : VINYL
- INSULATION COLOR : YELLOW
- TERMINAL MATERIAL : BRASS
- WIRE RANGE : 12-10 A.W.G. (  $4 - 6 \text{ mm}^2$  )
- NEMA TAB : 0.047 inch \* 0.370 inch (  $1.2 \text{ mm} * 9.40 \text{ mm}$  )
- DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
- TERMINAL SURFACE TREATMENT : TIN PLATED
- TERMINAL THICKNESS : 0.50 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm	$\pm 0.20$ ANGLE
6 > 18 mm	$\pm 0.30$ 0° REF ±
18 > 30 mm	$\pm 0.40$ ° ±
30 > 75 mm	$\pm 0.50$ ° ±

NAME	VINYL-FULLY INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS			UNIT	mm	
PART NO.	VFF5-375	MATERIAL	-----	APPROVE		
NUMBER	KA-95171-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2006/03/28	4/1	1-2	10F2	DRAWN	張馨尹