



REV	DESCRIPTION	DATE
△ RDK-96131		張馨尹 2008/01/09
△ RDK-98053		洗勝賢 2009/03/17

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	3	4	7	10
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : RED
  5. TERMINAL MATERIAL : BRASS
  6. WIRE RANGE : 22-16 A.W.G. ( 0.5-1.5 mm<sup>2</sup> )
  7. NEMA TAB : 0.032 inch \* 0.110 inch ( 0.8 mm \* 2.80 mm )
  8. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
  9. TERMINAL SURFACE TREATMENT : TIN PLATED
  10. TERMINAL THICKNESS : 0.40 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ±0.20	ANGLE
6 > 18 mm ±0.30	0° REF ±
18 > 30 mm ±0.40	° ±
30 > 75 mm ±0.50	° ±

NAME	VINYL-INSULATED DOUBLE CRIMP MALE DISCONNECTORS			UNIT	m
PART NO.	VM1-110-8	MATERIAL	-----	APPROVE	
NUMBER	KA-951327-C	SCALE	SHEET PAGE	CHECKED	
DATE	2006/09/11	4/1	1-2 10F2	DRAWN	張馨尹