



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2008/06/28
△	RDK-97127	張馨尹 2008/11/12
△	RDK-98020	謝婉如 2009/06/09
△	RDC-98308	謝婉如 2009/06/09
△	RDCM-109002	林淑楨 2020/02/12

NOTE :

1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	9	12	17	18
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : RED
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 22-16 A.W.G. ( 0.5-1.5 mm<sup>2</sup>)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.75 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED PIN TERMINALS				UNIT	mm	⊕	□
PART NO.	VPN1-12	MATERIAL	-----	APPROVE	張馨尹			
NUMBER	KA-970624-C	SCALE	REV.	SHEET	CHECKED	謝婉如		
DATE	2006/08/23	4/1	1-5	10F1	DRAWN	張馨尹		