



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2008/06/27
△	RDK-97127	張馨尹 2008/11/12
△	RDK-98020	謝婉如 2009/06/09
△	RDC-98308	謝婉如 2009/06/09

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16
AMP.	9	12	17	18
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : RED
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 22-16 A.W.G. (0.5-1.5 mm²)
 7. TERMINAL SURFACE TREATMENT : TIN PLATED
 8. TERMINAL THICKNESS : 0.75 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ±
>	mm ±
>	mm ±
>	mm ±
	ANGLE
	0° >
	° REF ±
	° ±
	° ±

NAME	VINYL-INSULATED PIN TERMINALS			UNIT	mm
PART NO.	VPN1-9	MATERIAL	-----	APPROVE	
NUMBER	KA-970622-C	SCALE	SHEET	PAGE	CHECKED
DATE	2006/08/23	4/1	1-4	10F1	DRAWN 張馨尹