



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2008/06/28
△	RDK-97127	張馨尹 2008/11/12
△	RDK-98020	謝婉如 2009/06/09
△	RDC-98308	謝婉如 2009/06/09

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14	
AMP.	18	30	
2. MAXIMUM ELECTRICAL RATING : \triangle 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.80 mm

\triangle Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED PIN TERMINALS				UNIT	mm
PART NO.	VPN2-12	MATERIAL	-----	APPROVE		
NUMBER	KA-970630-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2006/08/23	4/1	1-4	10F1	DRAWN	張馨尹