



REV	DESCRIPTION	DATE
△	RDK-97048	2009/08/20
△	RDK-97127	2009/08/20
△	RDK-98020	2009/08/20

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	9	12	17	18
  2. MAXIMUM ELECTRICAL RATING :  $105^{\circ}\text{C}$  600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : RED
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 22-16 A.W.G. (  $0.5-1.5 \text{ mm}^2$  )
  7. TERMINAL SURFACE TREATMENT : TIN PLATED
  8. TERMINAL THICKNESS : 0.75 mm

Tolerance Unless Otherwise Specified	
0 >	mm ±
>	mm ±
>	mm ±
>	mm ±
0°	° REF ±
>	° ±
>	° ±

NAME	VINYL-INSULATED (EASY ENTRY) RING TERMINALS				UNIT	mm
	VR1-6	MATERIAL		APPROVE		
NUMBER	KA-951244-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2006/09/06	4/1	1-3	10F2	DRAWN	