



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2009/04/13
△	RDK-97127	謝婉如 2009/04/13
△	RDK-98020	謝婉如 2009/04/13
△	RDJ-106043	林淑楨 2017/03/10

NOTE :

1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	9	12	17	18
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : RED
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 22-16 A.W.G. ( 0.5-1.5 mm<sup>2</sup> )
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.75 mm

Tolerance Unless Otherwise Specified	
0 >	mm ±
>	mm ±
>	mm ±
>	mm ±
	ANGLE
	0° REF ±
	° ±
	° ±

NAME	VINYL-INSULATED RING TERMINALS				UNIT	mm	
PART NO.	VR1-8	MATERIAL	-----	APPROVE			
NUMBER	KA-951079-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2006/08/31	4/1	1-4	10F1	DRAWN	張馨尹	