



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2009/05/13
△	RDK-97127	謝婉如 2009/05/13
△	RDK-98020	謝婉如 2009/05/13

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	16	14	
AMP.	18	30	
  2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
  3. INSULATION MATERIAL : VINYL
  4. INSULATION COLOR : BLUE
  5. TERMINAL MATERIAL : COPPER
  6. WIRE RANGE : 16-14 A.W.G. ( 1.5-2.5 mm<sup>2</sup> )
  7. TERMINAL SURFACE TREATMENT : TIN PLATED
  8. TERMINAL THICKNESS : 0.80 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED RING TERMINALS				UNIT	m
PART NO.	VR2-10	MATERIAL	-----	APPROVE	[Signature]	
NUMBER	KA-951488-C	SCALE	SHEET	PAGE	CHECKED	[Signature]
DATE	2007/01/12	3/1	1-3	10F2	DRAWN	張馨尹