



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2007/01/26
△	RDK-97127	謝婉如 2009/05/27
△	RDK-98020	謝婉如 2014/01/13
△	RDJ-106150	郭碧紋 2010/07/27

NOTE :

1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	16	14	
AMP.	18	30	
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 16-14 A.W.G. ( 1.5-2.5 mm<sup>2</sup> )
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.80 mm

△	Tolerance Unless Otherwise Specified
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED RING TERMINALS				UNIT	mm	
PART NO.	VR2-8	MATERIAL	-----	APPROVE			
NUMBER	KA-951487-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2007/01/12	4/1	1-4	10F1	DRAWN	張馨尹	