



| REV | DESCRIPTION | DATE           |
|-----|-------------|----------------|
| △   | RDK-97048   | 張馨尹 2008/06/03 |
| △   | RDK-97127   | 謝婉如 2009/04/27 |
| △   | RDK-98020   | 謝婉如 2009/04/27 |
| △   | RDJ-107485  | 林淑禎 2018/09/21 |

NOTE:

1. MAXIMUM ELECTRIC CURRENT : 

|        |    |    |  |
|--------|----|----|--|
| A.W.G. | 12 | 10 |  |
| AMP.   | 35 | 50 |  |
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : YELLOW
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 12-10 A.W.G.( 4-6 mm<sup>2</sup>)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 1.00 mm

|     |                                      |            |
|-----|--------------------------------------|------------|
| △   | Tolerance Unless otherwise Specified |            |
| 0 > | mm ±                                 | ANGLE      |
| >   | mm ±                                 | 0° ° REF ± |
| >   | mm ±                                 | ° ° ±      |
| >   | mm ±                                 | ° ° ±      |

|          |                                |          |       |         |         |     |   |   |
|----------|--------------------------------|----------|-------|---------|---------|-----|---|---|
| NAME     | VINYL-INSULATED RING TERMINALS |          |       |         | UNIT    | mm  | ⊙ | □ |
| PART NO. | VR5-5                          | MATERIAL | ----- | APPROVE | 張馨尹     |     |   |   |
| NUMBER   | KA-951524-C                    | SCALE    | REV.  | SHEET   | CHECKED | 楊輝耀 |   |   |
| DATE     | 2007/05/03                     | 4/1      | 1-4   | 10F1    | DRAWN   | 張馨尹 |   |   |