



REV	DESCRIPTION	DATE
△	RDK-97048	張馨尹 2008/06/03
△	RDK-97127	謝婉如 2009/04/27
△	RDK-98020	謝婉如 2009/04/27
△	RDCM-105167	林淑慎 2017/06/12

NOTE:

1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	12	10	
AMP.	35	50	
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : YELLOW
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 12-10 A.W.G.( 4-6 mm<sup>2</sup>)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 1.00 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ±
>	mm ±
>	mm ±
>	mm ±
ANGLE	
>	0° REF ±
>	° ±
>	° ±

NAME	VINYL-INSULATED RING TERMINALS				UNIT	mm	
PART NO.	VR5-6	MATERIAL	-----	APPROVE			
NUMBER	KA-951525-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2007/05/03	4/1	1-4	10F1	DRAWN	張馨尹	