



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2009/05/25
△	RDK-97127	謝婉如 2009/05/25
△	RDK-98020	謝婉如 2009/05/25

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : $\frac{\text{A.W.G. } 16 \mid 14}{\text{AMP. } 18 \mid 30}$
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : BLUE
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
 7. TERMINAL SURFACE TREATMENT : TIN PLATED
 8. TERMINAL THICKNESS : 0.80 mm

Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED RING TERMINALS			UNIT	mm
PART NO.	VRL2-37	MATERIAL	-----	APPROVE	
NUMBER	KA-951482-C	SCALE	SHEET	PAGE	CHECKED
DATE	2007/08/28	5/1	1-3	10F2	DRAWN 謝婉如