



REV	DESCRIPTION	DATE
△	RDK-97048	2008/05/30
△	RDK-97127	2009/04/27
△	RDK-98020	2009/04/27
△	RDJ-106346	2017/12/13

NOTE:

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	12	10	
AMP.	35	50	
2. MAXIMUM ELECTRICAL RATING : Δ 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : YELLOW
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 12-10 A.W.G.(4-6 mm²)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 1.00 mm

Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED RING TERMINALS				UNIT	mm	
PART NO.	VRL5-4	MATERIAL	-----	APPROVE			
NUMBER	KA-951523-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2007/05/03	4/1	1-4	10F1	DRAWN		