



| REV | DESCRIPTION | DATE |
|-----|-------------|----------------|
| △ | RDK-97048 | 謝婉如 2009/04/09 |
| △ | RDK-97127 | 謝婉如 2009/04/09 |
| △ | RDK-98020 | 謝婉如 2009/04/09 |

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : $\frac{\text{A.W.G.} \begin{matrix} |22 & |20 & |18 & |16 \\ \hline \text{AMP.} & |9 & |12 & |17 & |18 \end{matrix}}$
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : RED
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 22-16 A.W.G. (0.5-1.5 mm²)
 7. TERMINAL SURFACE TREATMENT : TIN PLATED
 8. TERMINAL THICKNESS : 0.75 mm

| △ Tolerance Unless Otherwise Specified | |
|--|-----------------|
| 0 > | mm ± ANGLE |
| > | mm ± 0° ° REF ± |
| > | mm ± ° ° ± |
| > | mm ± ° ° ± |

| | | | | | |
|----------|--------------------------------|----------|------------|---------|-----------|
| NAME | VINYL-INSULATED RING TERMINALS | | | UNIT | mm |
| PART NO. | VRM1-37 | MATERIAL | ----- | APPROVE | |
| NUMBER | KA-951073-C | SCALE | SHEET PAGE | CHECKED | |
| DATE | 2006/08/31 | 4/1 | 1-3 | 10F2 | DRAWN 張馨尹 |