



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2009/05/25
△	RDK-97127	謝婉如 2009/05/25
△	RDK-98020	謝婉如 2009/05/25

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14	
AMP.	18	30	
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.80 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED RING TERMINALS				UNIT	mm
PART NO.	VRS2-5	MATERIAL	-----	APPROVE	[Signature]	
NUMBER	KA-951484-C	SCALE	SHEET	PAGE	CHECKED	[Signature]
DATE	2007/07/02	5/1	1-3	10F2	DRAWN	張馨尹