



| REV | DESCRIPTION | DATE |
|-----|-------------|----------------|
| △ | RDK-97048 | 謝婉如 2008/06/27 |
| △ | RDK-97127 | 謝婉如 2009/04/07 |
| △ | RDK-98020 | 謝婉如 2009/04/07 |
| △ | RDCM-106003 | 林淑禎 2017/11/17 |

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

| | | |
|--------|----|----|
| A.W.G. | 16 | 14 |
| AMP. | 18 | 30 |
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : BLUE
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
 7. TERMINAL SURFACE TREATMENT : TIN PLATED
 8. TERMINAL THICKNESS : 0.80 mm

| | | |
|-----|--------------------------------------|----------|
| △ | Tolerance Unless otherwise Specified | |
| 0 > | mm ± | ANGLE |
| > | mm ± | 0° REF ± |
| > | mm ± | ° ± |
| > | mm ± | ° ± |

| | | | | | | | |
|----------|---------------------------------|----------|------------|---------|------|----|--|
| NAME | VINYL-INSULATED SPADE TERMINALS | | | | UNIT | mm | |
| PART NO. | VS2-32 | MATERIAL | ----- | APPROVE | | | |
| NUMBER | KA-95917-C | SCALE | SHEET PAGE | CHECKED | | | |
| DATE | 2006/07/18 | 4/1 | 1-4 10F1 | DRAWN | 張馨尹 | | |