



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2008/06/26
△	RDK-97127	謝婉如 2009/04/07
△	RDK-98020	謝婉如 2009/04/07

NOTE :

- MAXIMUM ELECTRIC CURRENT : $\frac{\text{A.W.G.} \begin{matrix} 12 & 10 \\ \text{AMP.} & 35 & 50 \end{matrix}}$
- MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
- INSULATION MATERIAL : VINYL
- INSULATION COLOR : YELLOW
- TERMINAL MATERIAL : COPPER
- WIRE RANGE : 12-10 A.W.G. (4-6 mm²)
- TERMINAL SURFACE TREATMENT : TIN PLATED
- TERMINAL THICKNESS : 1.00 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° ° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED SPADE TERMINALS				UNIT	
PART NO.	VS5-5	MATERIAL	-----	APPROVE		
NUMBER	KA-94019-C	SCALE	SHEET	PAGE	CHECKED	
DATE	2006/07/18	4/1	1-3	10F2	DRAWN	張馨尹