



REV	DESCRIPTION	DATE
△	RDK-97127	謝婉如 2009/04/07
△	RDK-98020	謝婉如 2009/04/07
△	RDC-99213	張馨尹 2010/06/03
△	RDCM-104133	郭碧紋 2015/10/06
△	RDCM-104133	林淑禎 2016/08/18

NOTE :

1. MAXIMUM ELECTRIC CURRENT : 

A.W.G.	16	14
AMP.	18	30
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : BLUE
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 16-14 A.W.G. ( 1.5-2.5 mm<sup>2</sup> )
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 0.80 mm

△	Tolerance Unless	
	Otherwise Specified	
0	> mm ±	ANGLE
>	mm ±	0° ° REF ±
>	mm ±	° ° ±
>	mm ±	° ° ±

NAME	VINYL-INSULATED SPADE TERMINALS				UNIT	mm	
PART NO.	VSL2-4	MATERIAL	-----	APPROVE			
NUMBER	KA-95923-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2006/07/18	4/1	1-6	10F2	DRAWN	張馨尹	