TELEPHONE: 01623 412 160 **E-MAIL:** SALES@TAKBRO.CO.UK

	н	D		ן ע ן		×
1				•	REV DESCRIPTION DATE ▲ RDK-97048 2008/09/11 ▲ RDK-97127 2008/09/11 ▲ RDK-98020 2009/08/2	15 1
5			5.5±0.20 Ø3.2-0 %			2
3		11.2±0.50			NOTE : 1. MAXIMUM ELECTRIC CURRENT : A.W.G. 22 20 18 16 AMP. 9 12 17 18 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX. 3. INSULATION MATERIAL : VINYL 4. INSULATION COLOR : RED 5. TERMINAL MATERIAL : COPPER	3 - 4
5		<u>Ø1.7±0.2</u> Ø4±0.3			6. WIRE RANGE : 22-16 A.W.G. (0.5-1.5 mm ²) 7. TERMINAL SURFACE TREATMENT : TIN PLATED 8. TERMINAL THICKNESS : 0.75 mm ▲ Tolerance Unless ▲ Dtherwise Specified 0 > mm ± 0°> ° REF±	5
6		4			→ mm ± → o ± → mm ± → o ± → mm ± → o ± NAME VINYL-INSULATED (EASY ENTRY) UNIT mm I DVR1-3 MATERIAL APPROVE NUMBER KA-951236-C SCALE SHEET PAGE CHECKED DATE 2006/09/06 4/1 1-3 10F2 DRAWN	6
×	A	В	C C		F F G H	

TAKBRO